

# Technical Data Sheet

## B-I-N<sup>®</sup> AQUA

**B-I-N<sup>®</sup> AQUA** is a ground-breaking water-based formula, developed for both professional and commercial applications.

- Ultra-low odour.
- Contains only trace VOCs (<0.1%).
- Interior and exterior use.
- Effectively primes, seals and blocks stains.
- Locks in problem odours.
- Superior adhesion without the need for sanding.
- Blocks knot stain and sap streaks

**Tinting:** **B-I-N<sup>®</sup> AQUA** can be tinted with up to 25ml of universal tinter per litre. Tinting the primer toward the colour of the topcoat helps it hide in one coat.

**Priming:** Use as a full-surface primer on wood panels, building boards, doors, frames, PVC, plywood, concrete, glossy paint and varnish, non-ferrous metal such as galvanised metal, copper, aluminium and stainless steel and other paintable surfaces.

**Spot-Priming:** **B-I-N<sup>®</sup> AQUA** is excellent for spot priming knots, resin, stains, etc, and is also ideal for interior spot priming of water stains. Note that the primer on spot-primed areas with a porous surface may show through if the topcoat has poor coverage. This also applies to many ceiling paints and shiny enamels – only use a topcoat with good coverage. For best results bring forward spot primed areas by allowing a minimum of 45 minutes for the spot primed area to dry before overcoating with a full coat of **B-I-N<sup>®</sup> AQUA** to the whole area, or to a natural break.

**Sealing:** **B-I-N<sup>®</sup> AQUA** penetrates and seals porous surfaces and dries to a smooth finish with excellent hiding properties. **B-I-N<sup>®</sup> AQUA** is an excellent primer for enamel and is ideal for wood, new cured plaster, concrete and concrete block, stucco, drywall, joint compound, uncoated wallcovering and other porous surfaces.

**Stain & Odour Blocking:** **B-I-N<sup>®</sup> AQUA** will effectively block stains from water, nicotine, grease, oil, soot, mildew, tannin, crayon and lipstick. **B-I-N<sup>®</sup> AQUA** is also an outstanding odour barrier and effectively blocks all types of odours including fire damage, smoke, nicotine, mildew, pet urine and odour from fireplaces and heaters.

**Fire Damage:** Replace severely charred substrates and remove loose soot and other contaminants with a dry chemical sponge or duster. Prime damaged surfaces with **B-I-N<sup>®</sup> AQUA** to block smoke stains, water stains, and seal odours.

**Knots & Sap Streaks:** Seal knots and resin with one to two coats of **B-I-N<sup>®</sup> AQUA**. If the wood is new, two coats are recommended.

**Glossy Surfaces:** Glossy enamel paint and clear finishes, cabinets, panelling, glass, Formica<sup>®</sup>, MDF, ceramic tile and non-ferrous metal can be primed without sanding or de-glossing.

**Surface Preparation:** Surfaces should be clean, dry, sound and free of any contamination, mildew, rust or unsound coatings that may interfere with adhesion. If unsure, wash surface with **Zinsser<sup>®</sup> Universal Degreaser & Cleaner**, rinse thoroughly and allow the surface to dry completely. Remove interior mould with **Zinsser<sup>®</sup> Mould Killer & Remover**. For exterior surfaces treat mould with a proprietary, exterior grade mould killer and remover in accordance with manufacturers instructions. Remove any peeling and/or unsound coatings. Sand any remaining paint film edges smooth. When priming over stained areas, first attempt to remove as much of the stain as possible by washing, sanding, scraping, etc. Allow surface to dry completely before priming. Substrate moisture content should not exceed 12%. New plaster which is polished or dusty should be sealed first with **Zinsser<sup>®</sup> Gardz<sup>®</sup>**. Degrease new galvanised steel with **Zinsser<sup>®</sup> Universal Degreaser & Cleaner** ensuring all traces of oil and surface contamination are removed. Unweathered powder coatings and Plastisol to be abraded and degreased thoroughly before priming. Special precautions should be taken during surface preparation of pre-1960s paint surfaces as they may contain harmful lead. Ensure application conditions are favourable and good painting practices are observed. Apply when air and surface temperature are between 7°C and 32°C with a relative humidity of less than 85%. Do not apply in direct sunlight or if condensation, rain, fog, frost etc. is likely to affect the freshly applied primer coat.

**Application:** Shake or stir well before use. Apply using a brush, roller or sprayer (follow manufacturer's instructions for sprayers; for airless spraying, use 0.015–0.017" tip at 1700-2200 psi). Thinning is not normally required, however, if necessary, add no more than 5% clean water. Do not thin if using for stain, knot or odour blocking.

**Dry Time:** At normal temperatures, **B-I-N® AQUA** is touch dry in 25 minutes and can be recoated in 45 minutes. Lower temperatures, higher humidity, and the addition of tint will prolong the dry and cure time of the product. For knots and stains, allow 2 hours to dry. When sealing water stains, some stains may appear in the primer as it dries, this is normal. Stains will be locked into the primer film and will not bleed into the topcoat.

**Coverage:** Up to 9m<sup>2</sup> per litre. Coverage may vary depending upon method of application and surface porosity.

**Cleanup:** Clean up spills and paint drips with warm soap and water. Wipe up splatters before they dry. Follow the equipment manufacturer's directions to clean spray equipment.

**Disposal:** Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Precautions:** Consult product Safety Data Sheet at [www.zinsseruk.com](http://www.zinsseruk.com) and refer to product label.

#### **Typical Physical Properties**

Percent Solids, Weight: 62%

Percent Solids, Volume: 46%

Density: 1.41 gram per milliliter

Viscosity Range: 100 to 105 KU

Theoretical Spread Rate: 9 sq. metres per litre

Touch Dry: 25 mins

Recoat: 45 mins

Full Cure: 7 days

VOC: EU limit value for this product (Cat: IIA/g.): 30 g/l.

This product contains max 1 g/l VOC.

Shelf Life: 3 years in unopened containers

Freeze/Thaw stable

Storage/Handling: Store indoors 5 - 30°C

**Limitations:** Not recommended for application to floors or decks, exterior roofs or to surfaces subject to immersion or prolonged contact with water. Not suitable for knots which are still actively exuding resin. Do not apply to steel or other ferrous metals as flash rusting will occur. This product will perform as claimed if applied according to our directions. The directions apply to most applications, but may not cover special conditions, applications, techniques and/or surfaces. If you have a question, check with your supplier or Zinsser® UK.

**Warranty:** **B-I-N® AQUA** is guaranteed to perform as indicated when applied according to label directions to a properly prepared surface. Direction areas complete as possible but cannot encompass all conditions, applications and / or surfaces beyond manufacture's control.



# SAFETY DATA SHEET

Zinsser B-I-N Aqua

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : Zinsser B-I-N Aqua  
**Product description** : Paint  
**Product type** : Liquid.  
**UFI** : P1H1-70XC-H00G-WME0

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Consumer use Industrial use Professional use	
Uses advised against	Reason
None identified.	-

### 1.3 Details of the supplier of the safety data sheet

RUST-OLEUM EUROPE  
 Martin Mathys NV, Kolenbergstraat 23, B-3545 Zelem, Belgium  
 Telephone no.: +32 (0) 13 460 200  
 Fax no.: +32 (0) 13 460 201

Tor Coatings Limited  
 Unit 21, White Rose Way, Follingsby Park, Gateshead, Tyne & Wear, NE10 8YX United Kingdom  
 Telephone no.: +44 (0) 191 4106611  
 Fax no.: +44 (0) 191 4920125  
 enquiries@tor-coatings.com

**e-mail address of person responsible for this SDS** : rpmeurohas@rustoleum.eu

### 1.4 Emergency telephone number

**National advisory body/Poison Centre**

**Supplier**

Telephone number United Kingdom: : +44 870 8200418 / +44 2038073798  
 Great Britain

Hours of operation : 24 / 7

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

**Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

Zinsser BIN Aqua

## SECTION 2: Hazards identification

<b>Signal word</b>	: No signal word.
<b>Hazard statements</b>	: No known significant effects or critical hazards.
<b>Precautionary statements</b>	
<b>General</b>	: P103 - Read carefully and follow all instructions. P102 - Keep out of reach of children. P101 - If medical advice is needed, have product container or label at hand.
<b>Prevention</b>	: Not applicable.
<b>Response</b>	: Not applicable.
<b>Storage</b>	: Not applicable.
<b>Disposal</b>	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
<b>Supplemental label elements</b>	: EUH208 - Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction. EUH210 - Safety data sheet available on request. EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
<b>Supplemental label elements : Detergents - Regulation (EC) No 907/2006</b>	: Not applicable.
<b>Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles</b>	: Not applicable.
<b>Special packaging requirements</b>	
<b>Containers to be fitted with child-resistant fastenings</b>	: Not applicable.
<b>Tactile warning of danger</b>	: Not applicable.

### 2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do not result in classification** : None known.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures** : Mixture

United Kingdom: Great Britain

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
1,2-benzisothiazol-3(2H)-one	REACH #: 01-2120761540-60 EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0,05	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411	ATE [Oral] = 490 mg/kg ATE [Inhalation (vapours)] = 0,5 mg/l Skin Sens. 1, H317: C ≥ 0,05% M [Acute] = 1	[1]

Date of issue/Date of revision

: 29/03/2023

Date of previous issue

: No previous validation

Version : 1

2/16

Zinsser BIN Aqua

### SECTION 3: Composition/information on ingredients

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	REACH #: 01-2120764691-48 CAS: 55965-84-9 Index: 613-167-00-5 List #: 611-341-5	<0,001	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410  <b>See Section 16 for the full text of the H statements declared above.</b>	ATE [Oral] = 64 mg/kg [1] ATE [Dermal] = 92,4 mg/kg ATE [Inhalation (dusts and mists)] = 0,171 mg/l Skin Corr. 1B, H314: C ≥ 0,6% Skin Irrit. 2, H315: 0,06% ≤ C < 0,6% Eye Dam. 1, H318: C ≥ 0,6% Eye Irrit. 2, H319: 0,06% ≤ C < 0,6% Skin Sens. 1, H317: C ≥ 0,0015% M [Acute] = 100 M [Chronic] = 100	[1]
---	--	--------	---	--	-----

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

List numbers have no legal significance.

This mixture contains ≥ 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
- Ingestion** : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Zinsser BIN Aqua

## SECTION 4: First aid measures

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire. In case of fire, use water spray (fog), foam, dry chemical or CO<sub>2</sub>.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst.
- Hazardous combustion products** : Decomposition products may include the following materials: metal oxide/oxides

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.
- Additional information** : No unusual hazard if involved in a fire.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

Zinsser BIN Aqua

## SECTION 6: Accidental release measures

**6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

### 7.1 Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8).  
**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 4 to 26°C (39,2 to 78,8°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

**Recommendations** : Not available.  
**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### DNELs/DMELs

## SECTION 8: Exposure controls/personal protection

Product/ingredient name	Type	Exposure	Value	Population	Effects
1,2-benzisothiazol-3(2H)-one  reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	DNEL	Long term Inhalation	6,81 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	1,2 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	0,966 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	0,345 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0,02 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	0,04 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Inhalation	0,02 mg/m <sup>3</sup>	General population	Local
	DNEL	Short term Inhalation	0,04 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Oral	0,09 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	0,11 mg/kg bw/day	General population	Systemic

### PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
titanium dioxide	Fresh water	0,127 mg/l	-
	Marine	>1 mg/l	-
	Sewage Treatment Plant	>100 mg/l	-
	Fresh water sediment	>1000 mg/kg	-
	Marine water sediment	>100 mg/kg	-
	Soil	100 mg/kg	-

## 8.2 Exposure controls

**Appropriate engineering controls** : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Use eye protection according to EN 166. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

### Skin protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.



## SECTION 8: Exposure controls/personal protection

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. > 8 hours (breakthrough time): nitrile rubber (0.5mm) gloves.  
The recommendation for the type or types of glove to use when handling this product is based on information from the following source: EN374. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Wear overalls or long sleeved shirt. (EN 467)
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour (Type A) and particulate filter (EN 140) .
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

- Physical state** : Liquid. [Viscous liquid.]
- Colour** : White.
- Odour** : Not available.
- Odour threshold** : Not available.
- Melting point/freezing point** : 0°C [Literature]
- Initial boiling point and boiling range** : >100°C (>212°F) [Literature]
- Flammability (solid, gas)** : Non-flammable in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and shocks and mechanical impacts. Nonflammable, but will burn on prolonged exposure to flame or high temperature.
- Lower and upper explosion limit** : Not available.
- Flash point** : Closed cup: 100°C (212°F) [Literature]
- Auto-ignition temperature** : Not relevant due to nature of the product.
- Decomposition temperature** : Not available.
- pH** : 5 [Conc. (% w/w): 100%] [OECD 122]
- pH : Justification** : Not available.
- Viscosity** : Dynamic: 1650 mPa·s [ASTM D562 [KU]]
- Solubility(ies)** :

Zinsser BIN Aqua

## SECTION 9: Physical and chemical properties

Media	Result
cold water	Soluble
hot water	Soluble
methanol	Very slightly soluble
acetone	Very slightly soluble

<b>Solubility in water</b>	: Not available.
<b>Partition coefficient: n-octanol/ water</b>	: Not applicable.
<b>Vapour pressure</b>	: 2,3 kPa (17,25 mm Hg) [Literature]
<b>Evaporation rate</b>	: <1 (butyl acetate = 1)
<b>Relative density</b>	: Not available.
<b>Density</b>	: 1,409 g/cm <sup>3</sup> [20°C (68°F)] [DIN 53217]
<b>Vapour density</b>	: >1 [Air = 1]
<b>Explosive properties</b>	: Non-explosive in the presence of the following materials or conditions: open flames, sparks and static discharge and heat. No unusual hazard if involved in a fire.
<b>Oxidising properties</b>	: Not available.
<b>Particle characteristics</b>	
<b>Median particle size</b>	: Not applicable.

## SECTION 10: Stability and reactivity

<b>10.1 Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>10.2 Chemical stability</b>	: The product is stable.
<b>10.3 Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.
<b>10.4 Conditions to avoid</b>	: No specific data.
<b>10.5 Incompatible materials</b>	: No specific data.
<b>10.6 Hazardous decomposition products</b>	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
1,2-benzisothiazol-3(2H)-one  reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	LC50 Inhalation Dusts and mists	Rat	0,11 mg/l	4 hours
	LC50 Inhalation Dusts and mists	Rat - Male, Female	0,5 mg/l	4 hours
	LD50 Oral	Rat - Male	490 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat - Male, Female	0,171 mg/l	4 hours
	LD50 Dermal	Rabbit	92,4 mg/kg	-

Zinsser BIN Aqua

## SECTION 11: Toxicological information

	LD50 Oral	Rat	64 mg/kg	-
--	-----------	-----	----------	---

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	490 64	N/A 92,4	N/A N/A	0,5 N/A	N/A 0,171

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Eyes - Severe irritant	Rabbit	-	-	-
	Skin - Severe irritant	Human	-	0.01 Percent	-
	Skin - Severe irritant	Rabbit	-	-	1 to 4 hours

### Conclusion/Summary

**Skin** : Based on available data, the classification criteria are not met.

**Eyes** : Based on available data, the classification criteria are not met.

**Respiratory** : Based on available data, the classification criteria are not met.

### Sensitisation

Product/ingredient name	Route of exposure	Species	Result
1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	skin skin	Guinea pig Guinea pig	Sensitising Sensitising

### Conclusion/Summary

**Skin** : Based on available data, the classification criteria are not met.

**Respiratory** : Based on available data, the classification criteria are not met.

### Mutagenicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Carcinogenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Reproductive toxicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Teratogenicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Zinsser BIN Aqua

## SECTION 11: Toxicological information

Not available.

### Aspiration hazard

Not available.

**Information on likely routes of exposure** : Routes of entry anticipated: Oral, Inhalation.  
Routes of entry not anticipated: Dermal.

### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards.  
**Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : No known significant effects or critical hazards.  
**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : No specific data.  
**Inhalation** : No specific data.  
**Skin contact** : No specific data.  
**Ingestion** : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

**Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

#### Potential chronic health effects

Not available.

**Conclusion/Summary** : Based on available data, the classification criteria are not met.  
**General** : No known significant effects or critical hazards.  
**Carcinogenicity** : No known significant effects or critical hazards.  
**Mutagenicity** : No known significant effects or critical hazards.  
**Reproductive toxicity** : No known significant effects or critical hazards.

## 11.2 Information on other hazards

### 11.2.1 Endocrine disrupting properties

Not available.

### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

Zinsser BIN Aqua

## SECTION 12: Ecological information

Product/ingredient name	Result	Species	Exposure
1,2-benzisothiazol-3(2H)-one  reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Acute EC50 0,11 mg/l	Algae	72 hours
	Acute EC50 0,067 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 0,9893 mg/l Marine water	Crustaceans - Opossum Shrimp	96 hours
	Acute EC50 2,94 mg/l Fresh water	Daphnia spec.	48 hours
	Acute LC50 2,18 mg/l Fresh water	Fish	96 hours
	Acute LC50 8 to 13 mg/l	Fish - Alburnus alburnus	96 hours
	Acute LC50 1,6 to 2,8 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 90 mg/l	Aquatic plants - Phaseolus vulgaris	20 days
	Chronic NOEC 1,2 mg/l	Daphnia spec.	21 days
	Chronic NOEC 0,21 mg/l	Fish	28 days
	Chronic NOEL 0,0403 mg/l	Algae	72 hours
	Acute EC50 0,037 mg/l Fresh water	Algae	48 hours
	Acute EC50 0,16 mg/l Fresh water	Daphnia spec.	48 hours
	Acute LC50 0,19 mg/l Fresh water	Fish	96 hours
Acute NOEC 0,004 mg/l Marine water	Algae	48 hours	
Chronic NOEC 0,18 mg/l	Daphnia spec.	21 days	
Chronic NOEC 0,02 mg/l Fresh water	Fish	38 days	

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	OECD 303A	>90 % - Readily - 1 days	-	-
	OECD 301D	>60 % - Readily - 28 days	-	-
	-	<50 % - 10 days	-	-

**Conclusion/Summary** : This product has not been tested for biodegradation. Based on available data, the classification criteria are not met.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	-	-	Readily Readily

### 12.3 Bioaccumulative potential

Zinsser BIN Aqua

## SECTION 12: Ecological information

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	0,64 -0.83 to 0.75	- -	low low

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Nonvolatile liquid.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Not available.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance.

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

#### European waste catalogue (EWC)

Waste code	Waste designation
08 01 12	waste paint and varnish other than those mentioned in 08 01 11

**Special precautions** : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Zinsser BIN Aqua

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
<b>14.1 UN number or ID number</b>	Not regulated.	Not regulated.	Not regulated.	Not regulated.
<b>14.2 UN proper shipping name</b>	-	-	-	-
<b>14.3 Transport hazard class(es)</b>	-	-	-	-
<b>14.4 Packing group</b>	-	-	-	-
<b>14.5 Environmental hazards</b>	No.	No.	No.	No.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to IMO instruments** : Not available.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Other EU regulations

- VOC** :
- VOC for Ready-for-Use Mixture** : IIA/g. Primers. EU limit value for this product : 30g/l (2010.)  
This product contains a maximum of 1 g/l VOC.
- Industrial emissions (integrated pollution prevention and control) - Air** : Not listed
- Industrial emissions (integrated pollution prevention and control) - Water** : Not listed

#### United Kingdom: Great Britain

##### UK (GB) /REACH

##### Annex XIV - List of substances subject to authorisation

###### Annex XIV

None of the components are listed.

###### Substances of very high concern

None of the components are listed.

##### Ozone depleting substances

Not listed.

##### Prior Informed Consent (PIC)

Not listed.

Zinsser BIN Aqua

## SECTION 15: Regulatory information

### Persistent Organic Pollutants

Not listed.

**Aerosol dispensers** :

### Seveso Directive

This product is not controlled under the Seveso Directive.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

### International regulations

#### Stockholm Convention on Persistent Organic Pollutants

List name	Ingredient name	Status
Not listed.		

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

List name	Ingredient name	Status
Not listed.		

**CN code** : 3209 10 00 00

### Inventory list

- Australia** : At least one component is not listed.
- Canada** : At least one component is not listed.
- China** : At least one component is not listed.
- Eurasian Economic Union** : **Russian Federation inventory**: Not determined.
- Japan** : **Japan inventory (CSCL)**: Not determined.  
**Japan inventory (ISHL)**: At least one component is not listed.
- New Zealand** : All components are listed or exempted.
- Philippines** : At least one component is not listed.
- Republic of Korea** : At least one component is not listed.
- Taiwan** : At least one component is not listed.
- Thailand** : Not determined.
- Turkey** : Not determined.
- United States** : At least one component is not listed.
- Viet Nam** : Not determined.

**15.2 Chemical safety assessment** : This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** :

- ATE = Acute Toxicity Estimate
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = CLP-specific Hazard statement
- N/A = Not available
- PBT = Persistent, Bioaccumulative and Toxic



Zinsser BIN Aqua

## SECTION 16: Other information

PNEC = Predicted No Effect Concentration  
 RRN = REACH Registration Number  
 SGG = Segregation Group  
 vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified.	

### Full text of abbreviated H statements

#### United Kingdom: Great Britain

#### Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

#### Full text of classifications [CLP/GHS]

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A

**Date of printing** : 29/03/2023

**Date of issue/ Date of revision** : 29/03/2023

**Date of previous issue** : No previous validation

**Version** : 1

### Notice to reader

**IMPORTANT NOTE:** The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates. Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

**MANUFACTURER'S DISCLAIMER:** the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Zinsser BIN Aqua

## **SECTION 16: Other information**

**Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.**