

3 STAGE FILTER REGULATOR

The new Anest Iwata 3 Stage filtration system is ideal for all modern day body shop and industrial environments.

- Adjustable Knob has snap-action lock for pressure setting.
- Innovative plug in design permits units to be removed from the line for extremely rapid servicing or replacement without disturbing pipe work.
- **60 cfm** provides more than enough air to run an air fed mask and two spray guns.
- The Body is Alloy die cast (Ambient temperature 90c) ideal for inside any spray booth.
- Pipe Threads ½ BSP.
- Recommended air flow 7-9 bar.
- Filter Regulator 5micron.
- Coalescent 0.01 Micron.
- Carbon 0.001 Micron.
- BS4275 British standards.



Model	
Capacity Air Flow	1698l/min (60cfm)
Max inlet flow	13 Bar (189psi)
Max outlet flow	0-8 bar (0-116psi)
Max operating temp	90c
Drain Valve	Semi Automatic
Max Pressure drop	5% of inlet pressure

ANEST IWATA UK LTD
Unit 10, Little End Road, Eaton Socon, St Neots, Cambridgeshire, PE19 8JH



Tel: 01480 405419 Fax: 01480 217610

www.anest-iwata.co.uk

enquires@anest-iwata.co.uk

ANEST IWATA MANUFACTURER OF SUPERNOVA