



A fine finish spray gun to provide ultra sensitive fan pattern control with the comfort of a full-size spray gun.

The DeVilbiss SRi *HD* is the ultimate fine finish spray gun providing superb feathering control combined with the pattern range and versatility needed for top quality fine finishing including spot repairs, shading and stencilling, whilst providing excellent comfort stability, balance and delicacy of control.

Typical Applications in General Industry

- Fine shading
- Retouching
- Stencilling
- Spot repair
- Reworking

Suitable for these materials

- Solvents and water based paints
- Stains and varnishes
- Inks and dyes
- Lacquers



Fine finish spray gun

A small scale fine finish spray gun with many practical uses throughout general industry, ergonomically styled for comfort.

- Choice of HVLP or Trans-Tech Compliant air caps provide superb atomisation of both solvent and waterbased materials
 - Stainless steel fluid tips & needles
 - Balanced air valve design for lighter trigger pull and improved air flow
 - Lightweight, strong, cast aluminium gun body
 - SRi is supplied as standard with a quality screw top gravity feed cup with 125mls. capacity
 - Optional inexpensive semi-disposable cups are available







SRi HD Compliant Trans-Tech Spray Gun

The SRi *HD* gun is constructed of the very highest grade alloys and stainless steels to ensure smooth operation as well as high impact resistance.

Every single component within the SRi *HD* spray gun is quality controlled and machined parts are checked to exacting tolerances.

Example of SRi *HD* spray gun part numbering: SRIHD-TS1-08 means...

SRIHD = SRI HD Gravity Gun / TS1 = TS1 Air cap / 08 = 0.8 fluid tip and needle

SRi HD Gravity Fluid Tip/ Needle (mm) sizes and code: 0.8, 1.0, 1.2, 1.4



Kit contents are spray gun c/w selected air cap and tip set up, gravity cup, pouring funnel, spanner, torx key and cleaning brushes.

Air cap Number and Type	Recommended Inlet Pressure	Air Flow @ recommended inlet pressure		
HS1 HVLP	2 bar (29psi)	135 l/min (5 scfm)		
TS1 Trans-Tech	2 bar (29psi)	100 l/min (4 scfm)		
RS1 Trans-Tech Round Spray	1 bar (15 psi)	55 I/min (2 scfm)		

SPECIFICATION	SRi HD Gravity
Air Connection	1/4" Universal
Gun Weight (with cup)	500g

For	turtner	tecnnicai	intormation	piease	reter t	o tne	5KI <i>HI</i>	Service	Bulletins

ITW Industrial Finishing

Ringwood Road, Bournemouth, England BH11 9LH Tel: +44 (0)1202 571111 Fax: +44 (0)1202 573488 Email: industrial.mktg@itwfinishing.co.uk

₹ Industrial Finishing

ITW Oberflächentechnik GmbH

Justus-von-Liebig-Strasse 31, 63128 Dietzenbach Germany Tel: +49 (0) 6074-403-1 Fax: +49 (0) 6074-403-281 Email: marketing@itw-finishing.de

ITW Surfaces et Finitions

163-171 Avenue des Auréats, BP 1453 26014 Valence cedex FRANCE Tel: +33(0)4 75 75 27 00 Fax: +33(0)4 75 75 27 59 Email: mkt@itwsf.com

www.itwifeuro.com